CS1782




2-Port USB 2.0 DVI KVMP Switch

The CS1782 DVI KVMP Switch charts a revolutionary new direction in KVM switch functionality by combining a 2-port KVM switch with a 2-port USB 2.0 hub at the same time as providing an interface for a DVI monitor and 7.1 channel surround sound support.



Setup -----

3 Keyboard/Mouse Combinations



Features

- 2-port DVI KVM Switch with USB 2.0 support and 7.1 channel surround sound audio
- One USB console controls two computers and two additional USB devices
- 2-port USB 2.0 hub built in
- USB 2.0 compliant
- Full bass response provides a rich experience for 7.1 channel surround sound systems
- Console audio ports on front panel for easy access ideal for IP phone users
- Independent switching of KVM, USB, and audio focus
- DVI digital and analog monitor support fully compliant with the DVI specifications; also HDCP compliant
- Superior video quality 2560 x 1600 (DVI Dual Link); 1920 x 1200(DVI Single Link)*
- Supports widescreen resolutions
- Computer selection via front panel pushbuttons and hotkeys
- Multiplatform support: Windows , Linux, Mac, and Sun
- Console mouse port emulation / bypass feature supports full mouse driver and multifunction mice
- Video DynaSync™- stores the console monitor's EDID(Extended Display Indentification Data) to optimize display resolution
- Complete keyboard emulation for error-free booting
- Sun/Mac keyboard support and emulation**
- Auto Scan Mode for monitoring all computers
- HDCP compliant
- Firmware upgradeable

*2560x1600@60Hz (DVI Dual Link);3840x2400@13Hz (DVI Single Link)only supports specific monitor resolution **1. PC keyboard combinations emulate Sun/Mac keyboards

Sun/Mac keyboards only work with their own computers

Specifications -----

Function				CS1782
Computer Connections				2
Port Selection				Hotkey; Pushbutton
Connectors	Console Ports	Keyboard		1 x USB Type A Female (Black)
		Mouse		1 x USB Type A Female (Black)
		Video		1 x DVI-I Female (White)
		Audio	Line Out	2 x Mini Stereo Jack Female (Green)
			Line In	1 x Mini Stereo Jack Female (Blue)
			Microphone	2 x Mini Stereo Jack Female (Pink)
			Side Speaker Out	1 x Mini Stereo Jack Female (Gray)
			Rear Speaker Out	1 x Mini Stereo Jack Female (Black)
			Center/Subwoofer	1 x Mini Stereo Jack (Orange)
	Computer Connectors	Keyboard / Mouse		2 x USB Type B Female (White)
		Video		2 x DVI-I Female (White)
		Audio	Line Out	2 x Mini Stereo Jack Female (Green)
			Line In	2 x Mini Stereo Jack Female (Blue)
			Microphone	2 x Mini Stereo Jack Female (Pink)
			Side Speaker Out	2 x Mini Stereo Jack Female (Gray)
			Rear Speaker Out	2 x Mini Stereo Jack Female (Black)
			Center/Subwoofer	2 x Mini Stereo Jack Female (Orange)
	USB Hub			2 x USB Type A Female (White)
	F/W Upgrade			1 x 4-conductor 3.5mm Jack (Black)
	Power			1 x DC Jack
Switches	Port Selection			2 x Pushbutton
LEDs	USB Link			2 (Green)
	On Line/Selected			2 (Orange)
Emulation	Keyboard/Mouse			USB
				DVI-D: 2560 x 1600 @60Hz(Dual Link)
Video Scan Interval				1920 x 1200@60Hz(Single Link)
			DVI-A: 2048 x 1536; DDC2B 1 - 99 secs. (5 secs. default)	
Power Consumption				DC5.3V, 4.8W
Environment	Operation Temp.			0-50°C
	Storage Temp.			-20-60°C
	Humidity			0-80% RH, Non-condensing
Physical Properties	Housing			Metal
	Weight			0.94 kg
	Dimensions (L x W x H)			27.00 x 8.70 x 5.50 cm

The specifications and pictures are subject to change without notice.

